

# Support. Upgrade. Maintenance.



AFT customers who have a Support, Upgrade, Maintenance (SUM) agreement are eligible to upgrade to most recent version at no extra cost. SUM agreements are 20% of the cost of new software; this means agreement holders receive the newest software at an 80% discount! Combined with training seminar discounts and access to premier support, the decision is easy. Call AFT to activate your SUM agreement today.



Releasing Spring 2018! AFT Fathom 10	AFT Fathom 9	AFT Fathom 8
Import from CAESAR II neutral files and Piping Component File (.pcf) as well as import/export model data from an EPANet file	New graphing features include display of multiple graphs in same tab, stacked graphs, double-Y axis graphs, and new graph folders to organize and easily display groups of saved graphs	Completely redesigned user interface with tabbed window access and new transparent icons
Enhanced Excel integration such as: Output data with a controlled scenario-to-worksheet Manager; improved import model change data with batch import to change multiple scenarios at once and use junction and parameter friendly names; easier Cost Database creation using Excel import/export	Language choices for German and Chinese, in addition to French and Spanish, for all output, graphs and menus	Improved printing features includes use of company logo, user comments and titles, as well as graphical borders on all printouts
Isometric grid drawing on the Workspace	Support for NFPA output reporting	New Quick Access Panel includes access to Scenario Manager
Made rotodynamic (centrifugal) and positive displacement pumps data entry clearer on the Pump Property window	GIS shape files can be imported to create a model	Handle varying ambient pressure with elevation allows for better understanding of gage pressure on submerged pipes at different depths
Acceleration head loss calculation for PD pumps	Improved search capability includes searches for pipe and junction notes, names and numbers	New Adjusted Turbulent K factor method allows for improved support of laminar pressure drop in fittings and valves
Enhanced pipe heat transfer including external convection coefficient calculation, buried pipe heat transfer, and heat tracing	New Weir junction	Robust support for two monitors
Large models now load faster	New 3-K method for laminar flow through fittings	New Startup panel allows user to choose engineering unit system (U.S./metric) and specify default fluid

Ready to access these new features? Email [info@aft.com](mailto:info@aft.com)